

C LF serija sa sušaćem i/ili frekventno reguliran 7.5 kW
Dobava zraka: 0.240-1.310 m³/min
Raspon tlaka: 7.5-13 bara

Tip	Maksimalni tlak bar	Volumen spremnika/ lit	Efektivna dobava zraka m ³ /min	Snaga motora		Dimenzije u mm ŠxDxV	Težina kg
				kW	KS		
C 9 LF	7.5		0.26-1.31	7.5	10	1020x532x723	200
C 9 LF	8		0.26-1.27	7.5	10	1020x532x723	200
C 9 LF	10		0.25-1.12	7.5	10	1020x532x723	200
C 9 LF	13		0.24-0.93	7.5	10	1020x532x723	200
C 9 LFR	7.5	270	0.25-1.31	7.5	10	1720x790x1365	315
C 9 LFR	8	270	0.26-1.27	7.5	10	1720x790x1365	315
C 9 LFR	10	270	0.25-1.12	7.5	10	1720x790x1365	315
C 9 LFR	13	270	0.24-0.93	7.5	10	1720x790x1365	323
C 9 LFDR	7.5	270	0.25-1.31	7.5	10	1720x745x1320	362
C 9 LFDR	8	270	0.26-1.27	7.5	10	1720x745x1320	362
C 9 LFDR	10	270	0.25-1.12	7.5	10	1720x745x1320	362
C 9 LFDR	13	270	0.24-0.93	7.5	10	1720x745x1320	387

Emitirana buka kompresora je prema DIN EN ISO 2151:2009: **72 dB(A)**