

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

| BOGE type | Max. pressure bar | Effective free air delivery m ³ /min | Rated output | | Dimensions W x D x H (mm) | Compressed-air outlet | Weight with sound insulation kg | Weight with super sound insulation kg |
|------------|----------------------|--|------------------|-----------------|------------------------------|-----------------------|------------------------------------|--|
| | | | Main drive kW | Fan motor kW | | | | |
| S 56-4 LF | 7.5 | 2.8 - 10.9 | 55 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 56-4 LF | 10 | 2.5 - 9.0 | 55 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 56-4 LF | 13 | 2.3 - 7.2 | 55 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 56-4 L | 7.5 | 10.1 | 55 | 2.2 | 2330 x 1420 x 1990 | DN 65 | 2070 | 2090 |
| S 76-4 | 7.5 | 14.1 | 75 | 2.2 | 2330 x 1420 x 1990 | DN 65 | 2160 | 2180 |
| S 76-4 | 10 | 12.5 | 75 | 2.2 | 2330 x 1420 x 1990 | DN 65 | 2160 | 2180 |
| S 76-4 | 13 | 10.4 | 75 | 2.2 | 2330 x 1420 x 1990 | DN 65 | 2160 | 2180 |
| S 76-4 LF | 7.5 | 2.9 - 14.4 | 75 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 76-4 LF | 10 | 2.8 - 12.3 | 75 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 76-4 LF | 13 | 2.6 - 10.4 | 75 | 2.2 | 2380 x 1420 x 1990 | DN 65 | 2150 | 2170 |
| S 90-4 | 7.5 | 16.5 | 90 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2260 | 2280 |
| S 90-4 | 10 | 15.0 | 90 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2260 | 2280 |
| S 90-4 | 13 | 12.6 | 90 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2260 | 2280 |
| S 90-4 LF | 7.5 | 2.9 - 16.6 | 90 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 90-4 LF | 10 | 2.8 - 14.7 | 90 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 90-4 LF | 13 | 2.7 - 12.8 | 90 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 110-4 | 10 | 17.1 | 110 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2260 | 2280 |
| S 110-4 | 13 | 15.2 | 110 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2260 | 2280 |
| S 110-4 LF | 7.5 | 5.8 - 19.2 | 110 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 110-4 LF | 10 | 2.8 - 16.3 | 110 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 110-4 LF | 13 | 2.8 - 14.4 | 110 | 3.0 | 2380 x 1420 x 1990 | DN 65 | 2250 | 2270 |
| S 110-4 L | 7.5 | 19.3 | 110 | 3.0 | 2330 x 1420 x 1990 | DN 65 | 2170 | 2190 |

BOGE S-4 series

Designed to take the lead



TECHNICAL DATA

| BOGE type | Max. pressure bar | Effective free air delivery m ³ /min | Rated output | | Dimensions W x D x H (mm) | Compressed-air outlet | Weight with sound insulation kg | Weight with super sound insulation kg |
|------------|----------------------|--|------------------|-----------------|------------------------------|-----------------------|------------------------------------|--|
| | | | Main drive kW | Fan motor kW | | | | |
| S 111-4 | 7.5 | 20.5 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 | 10 | 17.5 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 | 13 | 14.4 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 7.5 | 5.5 - 21.1 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 10 | 5.3 - 18.5 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 LF | 13 | 4.9 - 14.4 | 110 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 111-4 L | 7.5 | 20.5 | 110 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3450 | 3500 |
| S 132-4 | 7.5 | 24.1 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 | 10 | 21.7 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 | 13 | 17.2 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 7.5 | 5.5 - 25.0 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 10 | 5.3 - 21.8 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 LF | 13 | 5.0 - 17.9 | 132 | 3.0 | 2980 x 1620 x 1990 | DN 80 | 3650 | 3700 |
| S 132-4 L | 10 | 20.2 | 132 | 3.0 | 2930 x 1620 x 1990 | DN 80 | 3550 | 3600 |
| S 160-4 | 7.5 | 28.1 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 | 10 | 25.0 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 | 13 | 21.2 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3700 | 3750 |
| S 160-4 LF | 7.5 | 5.5 - 27.7 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 LF | 10 | 5.3 - 25.1 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 LF | 13 | 5.0 - 21.2 | 160 | 5.5 | 2980 x 1620 x 1990 | DN 80 | 3750 | 3800 |
| S 160-4 L | 13 | 19.3 | 160 | 5.5 | 2930 x 1620 x 1990 | DN 80 | 3600 | 3650 |