



Sušači DS serije

BOGE Type	Flow Capacity			Maximum Pressure bar	Pressure Difference at Full Load		Power Consumption		Installed Capacity		Compressed Air Connection	Cooling Air Volume		Dimensions W x D x H		Weight kg
	m ³ /min	m ³ /h	cfm		bar	psig	kW	PS	kW	PS		m ³ /h	cfm	mm	mm	
DS 120	12.00	720	424	14	0.130	1.885	1.13	1.54	2.38	3.42	G 2	2800	1646	706x1046x1064	145	
DS 140	14.00	840	494	14	0.180	2.610	1.14	1.55	2.38	3.42	G 2	2800	1646	706x1046x1064	145	
DS 180	18.00	1080	636	14	0.230	3.335	1.46	1.99	3.02	4.11	G 2	4000	2352	706x1046x1064	155	
DS 220	22.00	1320	777	14	0.090	1.305	1.68	2.28	3.41	4.64	G 2 1/2	7050	4145	806x1166x1316	230	
DS 260	26.00	1560	918	14	0.130	1.885	2.19	2.98	4.47	6.08	G 2 1/2	7050	4145	806x1166x1316	240	
DS 300	30.17	1810	1065	14	0.170	2.465	2.41	3.28	5.27	7.17	G 2 1/2	7050	4145	806x1166x1316	245	
DS 350	35.00	2100	1236	14	0.240	3.480	3.06	4.16	6.26	8.51	G 2 1/2	7050	4145	806x1166x1316	250	
DS 460	46.00	2760	1624	14	0.140	2.030	3.14	4.27	6.26	8.51	DN 100	7050	4145	1007x1245x1723	470	
DS 520	52.00	3120	1836	14	0.180	2.610	3.54	4.81	7.46	10.15	DN 100	7050	4145	1007x1245x1723	490	
DS 630	63.00	3780	2225	14	0.260	3.770	4.64	6.31	9.92	13.49	DN 100	14100	8291	1007x1657x1810	580	
DS 750	75.00	4500	2648	14	0.160	2.320	5.73	7.79	11.32	15.40	DN 150	14100	8291	1007x1657x1810	670	
DS 900	90.00	5400	3178	14	0.230	3.335	7.63	10.38	16.26	22.11	DN 150	19000	11172	1007x1657x1810	690	
DS 1200	120.00	7200	4237	14	0.230	3.335	8.92	12.13	19.26	26.19	DN 150	19000	11172	1007x1657x1807	830	
DS 1500	150.00	9000	5297	14	0.200	2.900	12.35	16.80	25.64	34.87	DN 200	28500	16758	1007x2257x2208	1100	
DS 1800	180.00	10800	6356	14	0.260	3.770	15.96	21.71	31.04	42.21	DN 200	28500	16758	1007x2257x2208	1190	